

## ABC STORED PRESSURE TYPE FIRE EXTINGUISHERS A SURE SHORT SOLUTION FOR ALL TYPE OF FIRES



We understand that fire fighting is not a piece of cake. One should know the class of fire before dousing it, or else the fire extinguisher could do more damage than the fire itself.

In order to keep such situations at bay & quell fires effectively, we have created mono-ammonium phosphate powder based extinguishers that take such uncertainties out of the equation. Being a multipurpose firefighting agent, it extinguishes Class – A, B, C & electrically started fires, with ease.

So that when you douse fire, you can forget about its class & simply concentrate your energies to knock it down.

WORKS ON



Solid Combustible  
Fires



Flammable Liquid  
Fires



Flammable Gases



Electrically  
Started Fires

# We're just enthusiastic about what we do

IS : 15683



CM/L-2529155



## KEY FEATURES

- SIMPLE OPERATION & EASY TO MAINTAIN
- EASY SNAP SEAL WITH SQUEEZE GRIP VALVE
- STATE OF THE ART PRESSURE GAUGE

## TECHNICAL SPECIFICATIONS

MODEL	AS-1	AS-2	AS-4	AS-6	AS-9
Capacity (in Kg.)	1	2	4	6	9
Anti-Corrosive Inhibitor	Epoxy Polyester Powder Coating	Epoxy Polyester Powder Coating	Epoxy Polyester Powder Coating	Epoxy Polyester Powder Coating	Epoxy Polyester Powder Coating
Conforming IS Code	15683	15683	15683	15683	15683
Type of Extinguisher Media	Dry Powder IS 14609	Dry Powder IS 14609	Dry Powder IS 14609	Dry Powder IS 14609	Dry Powder IS 14609
Expellent	Pressurized with N <sub>2</sub> gas	Pressurized with N <sub>2</sub> gas	Pressurized with N <sub>2</sub> gas	Pressurized with N <sub>2</sub> gas	Pressurized with N <sub>2</sub> gas
Minimum Effective Discharge(%)	85	85	85	85	85
Minimum Jet Length(Mtrs.)	More than 2 mtr	More than 2 mtr	More than 2 mtr	More than 2 mtr	More than 2 mtr
Discharge Time (in Sec.)	More than 8 sec	More than 13 sec	More than 13 sec	More than 13 sec	More than 13 sec
Hydraulic Test Pressure (in Kgf/cm <sup>2</sup> )	35	35	35	35	35
Operating Position	Upright	Upright	Upright	Upright	Upright
Operating Temperature Range (°c)	(-)10 to (+)55	0 to (+)55	0 to (+)55	0 to (+)55	0 to (+)55
Operating Valve	Squeeze Grip with Nozzle	Squeeze Grip with Nozzle	Squeeze Grip with Discharge Hose & Nozzle	Squeeze Grip with Discharge Hose & Nozzle	Squeeze Grip with Discharge Hose & Nozzle
Fire Rating	1A & 8B	1A & 8B	2A & 21B	3A & 21B	4A & 34B

Other available brands : Blot Fire & Fire Escort



## GLOBAL SAFETY SOLUTIONS

New Delhi - 110064  
Website : [www.firesafetyproducts.co.in](http://www.firesafetyproducts.co.in)

Channel Partner

ABC STORED PRESSURE TYPE FIRE EXTINGUISHERS